

Features & Advantages

- ▶ Its air tightness passed rigorous smoke isolation test in the close state.
- ▶ It can be linked with the fan motor to realize zero wind resistance operation in the fully open state.
- ▶ Strong pressure resistance, can long-term bear strong wind making by high negative pressure fan without deformation.
- ▶ High-strength plastic coupling and aluminum alloy body, with anti-corrosion to be adapted to all kinds of harsh animal husbandry environment, or marine environment.
- ▶ Length and width can be customized according to demands.



Electric rolling door



When reaches the positioning, the motor power is cut off and self-locking

| Model No. | | JMN18" | | JMN24" | | JMN36" | | JMN50" | | JMN51" | | JMN57" | |
|-------------------------|------------------------------|-----------------|----|---------------|----|---------------|----|---------------|----|---------------|----|---------------|----|
| Motor data | Volts (V) | 220 | | 220 | | 220 | | 220 | | 220 | | 220 | |
| | Hertz (HZ) | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 |
| | Rated current (A) | 0.64 | | 0.64 | | 0.99 | | 0.99 | | 0.99 | | 0.99 | |
| | Power (W) | 145 | | 145 | | 228 | | 228 | | 228 | | 228 | |
| | Operation time consuming (S) | Full open | 11 | | 14 | | 19 | | 23 | | 24 | | 26 |
| Full closed | | 11 | | 14 | | 19 | | 23 | | 24 | | 26 | |
| Features | Frame | Aluminium alloy | | | | | | | | | | | |
| | Shutter piece | PVC | | | | | | | | | | | |
| | Bracket | Coated steel | | | | | | | | | | | |
| Overall dimensions (mm) | | 950*1170*255 | | 1130*1350*255 | | 1430*1715*255 | | 1790*2010*255 | | 1830*2050*255 | | 1980*2200*255 | |
| Opening dimensions (mm) | | 730*730 | | 910*910 | | 1270*1270 | | 1570*1570 | | 1610*1610 | | 1760*1760 | |