

Standard sizes Rod and Tube

Medidas de catálogo - Barra

CuSn7Zn4Pb7-C (CC493K) EN 1982

W-7

Standard sizes (mm) Rod and Tube

Medidas de catálogo - Barra (mm)

OD Øext.	ID Øint.							
16	0							
21	0							
26	0	14						
31	0	14	19					
36	0	14	19	24				
41	0	14	19	24	29			
46	0	14	19	24	29	34		
51	0	19	24	29	34	39		
56	0	24	29	34	39	44		
61	0	19	24	29	34	39	44	
66	0	19	29	34	39	44	49	
71	0	19	24	29	34	39	44	49
76	0	29	34	39	44	49	54	59
82	0	28	33	38	43	48	53	58
87	0	28	33	38	43	53	58	63
92	0	28	38	48	58	68	73	
97	0	48	58	63	68	73		
102	0	28	38	48	58	68	73	78
107	83							
112	0	38	48	58	68	73	78	83
117	0							
122	0	48	58	68	78	88		
127	0							
132	0	58	68	78	88	98	108	
142	0	58	68	78	88	98	108	
152	0	58	68	78	88	98	108	118
162	0	78	88	98	108	118	128	
172	0	68	98	128	138			
182	0	78	98	118	138			
192	0	98	128	138	148			
202	0	98	118	128	138	148	158	
212	0	108	148	158	168			
222	0	98	138	168				
232	0	118	148	168	178			
242	178							
252	0	198						
262	0	158	198	208				
272	0							
282	0	138	178	198	208			
292	218							
303	0	197						
323	0							
333	0							

Standard delivery lengths (mm)

Longitudes estándar de suministro (mm)

1000, 2000, 3050

Diameter tolerances (mm)

Tolerancias para los diámetros (mm)

OD Øext.	Tolerances Tolerancias	
	OD Øext.	ID Øint.
13 - 76	+ 0,5 - 0,0	+ 0,0 - 1,0
77 - 102	+ 1,0 - 0,0	
103 - 142	+ 2,0 - 0,0	+ 0,0 - 2,0
143 - 242		
243 - 252	+ 3,0 - 0,0	+ 0,0 - 3,0
253 - 333		

Length tolerances (mm)

Tolerancias para la longitud (mm)

Length Longitud	Tolerances Tolerancias
< 1000	+ 5 - 0
≥ 1000	+ 50 - 0

Geometric tolerances

Tolerancias geométricas

OD Øext.	Tolerances Tolerancias		
	Roundness Redondez mm	Eccentricity Excentricidad mm	Straightness Rectitud mm/m
13 - 102	≤ 0,7	≤ 0,7	≤ 1,2
103 - 172			≤ 1,5
173 - 333		≤ 1,0	

**We make any other size on request
Contact us**

Standard sizes Rod and Tube

Medidas de catálogo - Barra

CuSn11Pb2-C (CC482K) EN 1982

W-12Zn

Standard sizes (mm) Rod and Tube

Medidas de catálogo - Barra (mm)

OD Øext.	ID Øint.							
16	0							
21	0							
26	0	14						
31	0	14	19					
36	0	14	19	24				
41	0	14	19	24	29			
46	0	19	24	29	34			
51	0	19	24	29	34	39		
56	0	24	34	39				
61	0	19	24	29	34	39	44	
66	0	19	29	39	44	49		
71	0	29	34	39	44	49		
76	0	29	39	49	54	59		
82	0	28	33	38	48	53	58	63
87	0	33	38	53	58	68		
92	0	28	38	48	58	68	73	
97	0	58	73					
102	0	28	38	48	58	68	73	78
112	0	38	48	58	68	78	88	
117	0							
122	0	48	58	68	78	88		
127	0							
132	0	68	78	88	98	108		
142	0	58	68	78	88	98	108	
152	0	68	78	88	98	108	118	
162	0	78	88	98	108	118	128	
172	0	68	98	128	138			
182	0	78	98	118	138			
192	0	98	128	148				
202	0	98	118	138	158			
212	0	148	168					
222	0	98	138					
232	0	118	148	178				
242	178							
252	0	198						
262	0	158	198	208				
282	0	138	198	208				
292	218							
303	0	197						
333	0							

We make any other size on request
Contact us

Standard delivery lengths (mm)

Longitudes estándar de suministro (mm)

1000, 2000, 3050

Diameter tolerances (mm)

Tolerancias para los diámetros (mm)

OD Øext.	Tolerances Tolerancias	
	OD Øext.	ID Øint.
13 - 76	+ 0,5 - 0,0	+ 0,0 - 1,0
77 - 102	+ 1,0 - 0,0	
103 - 142		+ 0,0 - 2,0
143 - 242	+ 2,0 - 0,0	
243 - 252	+ 3,0 - 0,0	
253 - 333		+ 0,0 - 3,0

Length tolerances (mm)

Tolerancias para la longitud (mm)

Length Longitud	Tolerances Tolerancias
< 1000	+ 5 - 0
≥ 1000	+ 50 - 0

Geometric tolerances

Tolerancias geométricas

OD Øext.	Tolerances Tolerancias		
	Roundness Redondez mm	Eccentricity Excentricidad mm	Straightness Rectitud mm/m
13 - 102	≤ 0,7	≤ 0,7	≤ 1,2
103 - 172			≤ 1,5
173 - 333		≤ 1,0	