

CARTOPACK

Pneumatic heat sealer for laminated bags

The Cartopack is a powerful pneumatic sealer for medium to big sized bags of any sealable laminate material (Paper/PE, AL/PE,...) in short or average productions.

The temperature of the jaws and the sealing time can be adjusted to suit the type and thickness of the material to be sealed.

The new Cartopack incorporates the following improvements:

- Digital electronic controller with incorporated microprocessor.
- 2 line LCD retroilluminated screen and user-friendly polycarbonate control panel, for an easy adjustment of the working parameters (temperature, sealing time, counters,...).
- Electrical cabinet IP65.

The sealer is pneumatically operated and requires connection to compressed air with 6 bar pressure.

By pressing the foot pedal the sealing bars will close for the set time and then open automatically. The 2 profiled sealing bars are both heated and apply high pressure to obtain 15 mm. seal of perfect quality.

The CARTOPACK is manufactured in two sealing lengths: 450 mm. and 600 mm.

- Accessory: Support with a work table.
- Materials: All kind of sealable paper and aluminium.
- Option: CARTOPACK VACUUM and CARTOPACK VACUUM-GAS.



Cartopack 600 inox with support with work table

TECHNICAL SPECIFICATIONS:	CARTOPACK-450	CARTOPACK-600
Seal width (mm.):	15	15
Seal length (mm.):	450	600
Voltage (V.):	230	230
Consumption (W.):	900	1100
Dimension of packed machine (mm.):	600 x 900 x 800	1100 x 600 x 800
Dimension of packed machine and support:	1600 x 1100 x 800	1600 x 900 x 800