



聚氨酯圆带系列包括光面圆带、粗面圆带，规格从  $\Phi 2 \sim \Phi 20\text{mm}$ 。粗面圆带为绿色，其表面粗糙颗粒均匀整齐，手感舒适；光面圆带为橙色，其表面光洁度好，色泽鲜艳。

Polyurethane round belt can be smooth or rough surface with the diameter from 2mm-20mm. Rough finish round belt is green color. the surface is superior performance. Smooth finish round belt is popular orange color, the finish surface is glossy

■ 产品特点:

- 极高的抗张力、拉力强度
- 耐磨耗、耐冲击、防油、防水
- 耐化学性
- 不含可塑性
- 使用温度范围广
- 不易伸长
- 易熔接、易安装
- 寿命长

■ Product features

- High tensile and tear strength
- Wear resistance, impact resistance, oil proof, water proof
- Chemical resistance
- No plasticizers
- Broad temperature range
- Low elongation
- Fast joining, easily install
- Long life


| 直径<br>Diameter<br>(mm) | 最小带轮直径<br>Min. pulley dia. |     | 延伸率<br>Elongation | 最大拉伸强度<br>Max. tensile strength |     | 夹芯<br>core |
|------------------------|----------------------------|-----|-------------------|---------------------------------|-----|------------|
|                        | in                         | mm  |                   | kg                              | lb  |            |
| 2                      | 0.75                       | 20  | 1.5~3%            | 0.3                             | 0.7 | .          |
| 3                      | 1                          | 25  | 1.5~3%            | 0.7                             | 1.6 | .          |
| 4                      | 1.25                       | 35  | 1.5~3%            | 1.2                             | 2.7 | .          |
| 5                      | 1.5                        | 40  | 1.5~3%            | 2                               | 4.3 | .          |
| 6                      | 2                          | 50  | 1.5~3%            | 3.2                             | 7   | .          |
| 7                      | 2.25                       | 55  | 1.5~3%            | 4.1                             | 9   | .          |
| 8                      | 2.5                        | 65  | 1.5~3%            | 5                               | 11  | .          |
| 9                      | 3                          | 75  | 1.5~3%            | 6.8                             | 15  | .          |
| 10                     | 3                          | 75  | 1.5~3%            | 7.7                             | 17  | .          |
| 12                     | 4                          | 100 | 1.5~3%            | 12.2                            | 27  | .          |
| 15                     | 4.75                       | 120 | 1.5~3%            | 17.7                            | 39  | .          |
| 18                     | 5.7                        | 145 | 1.5~3%            | 25.4                            | 56  | .          |
| 20                     | 6.25                       | 160 | 1.5~3%            | 31.3                            | 69  | .          |

材质 Material: PU

表面纹理 Surface: 粗糙, 光滑 rough, smooth

颜色 Color: 绿色, 橙色, 蓝色, 黑色, 黄色, 透明, 红色 green, orange, blue, black, yellow, transparent, red

硬度 Hardness: 邵氏 70A-98A shore 70A~98A



接驳 Joint system

聚氨酯三角带 PU triangular belt

| 型号 Specification | X(mm) | H(mm) | M/ 卷 M/rolls | 夹芯 Reinforced cord |
|------------------|-------|-------|--------------|--------------------|
| A                | 13    | 8     | 50           | ●                  |
| B                | 17    | 11    | 50           | ●                  |
| C                | 22    | 14    | 50           | ●                  |
| D                | 32    | 19    | 50           | ●                  |
| M                | 8     | 4     | 50           | ●                  |
| Z                | 10    | 5     | 50           | ●                  |

聚氨酯花纹带 PU super grip belt

| 型号 Specification | X(mm) | H(mm) | Z(mm) | M/ 卷 M/rolls | 夹芯 Reinforced cord | 表面 PVC 花纹 With PVC Pattern |
|------------------|-------|-------|-------|--------------|--------------------|----------------------------|
| A                | 13    | 8     | 3.5   | 50           | ●                  | ●                          |
| B                | 17    | 11    | 3.5   | 50           | ●                  | ●                          |
| C                | 22    | 14    | 3.5   | 50           | ●                  | ●                          |
| D                | 32    | 19    | 3.5   | 50           | ●                  | ●                          |
| M                | 8     | 4     |       | 50           | ●                  | ●                          |
| Z                | 10    | 5     | 3.5   | 50           | ●                  | ●                          |

聚氨酯五角带 PU pentagonalbelt

| 型号 Specification | X(mm) | H(mm) | 硬度 Hardness(A) | M/ 卷 M/rolls | 夹芯 Reinforced cord |
|------------------|-------|-------|----------------|--------------|--------------------|
| A                | 13    | 17    | 90             | 30           | ●                  |
| B                | 17    | 22    | 90             | 30           | ●                  |
| C                | 22    | 28    | 90             | 30           | ●                  |

