




Digital Label Finishing System

- Fully servo driven flexo unit.
- Flexo printing, cold foil, lamination, varnish and super varnish.
- Servo driven die cutting with automatic registration system.
- Exchanged between full-rotary and semi-rotary mode.
- Hot air(I/R) dryer.
- Optional for IML, water-based primer, coating, lamination etc.

Digital Label Finishing System



TECHNICAL SPECIFICATIONS

Max web width	340/430mm
Max unwind diameter	700mm
Max dual rewind diameter	600mm
Max die cutting width	330/420mm
Semi-rotary max speed	70m/min
Max semi-rotary repeat length	457mm
Max mechanical speed	130m/min
Die cutting registration tolerance	±0.15mm
Rating voltage	3PH+N+PE
Size(length x width x height)	4.1×2.1×1.7m
Machine weight	2.5T

CONTACT US

BROTECH DIGITAL GRAPHICS CO.,LTD

Shenzhen Headquarter : 1st Floor, 8th Building, TongFuYu Industrial Park, YongHe Road, Fuyong town, Baoan District, Shenzhen, China. Tel: +86-755-8373 3867

Jiangsu Factory : No.1 YangFan Road, New District, Zhenjiang, Jiangsu, China. Tel: +86-511-8880 0886

BROTECH DIGITAL GRAPHICS NORTH AMERICA

1203 Murdock Ct Naperville, IL 60540 Tel: +1630 7190 1968

tectuPRINT

Brotech

