

WHEEL SERIES

NFA

- Polyamide (Nylon 6) with Fiber glass
- Plain bearing

NFC

- Polyamide (Nylon 6) with Fiber glass
- Double ball bearing

NF

General technical characteristics

Wheel material	White Polyamide (Nylon 6) with fiber glass
Type of bearing:	Plain bearing Ball bearing
Center:	Polyamide
Thermal range	-15C / + 80C
Thread hardness:	90shA




We serve the needs of the application



NFA
PLAIN BEARING

NFC
BALL BEARINGS



Properties

Resistance to chemicals
Resistance in wet conditions
Long service life

M series Medium range

50	24	8	28	50	≡
50	24	8	28	50	◻◻
75	24	8	28	60	≡
75	24	8	28	60	◻◻
100	24	8	28	70	≡
100	24	8	28	70	◻◻
125	24	8	28	80	≡
125	24	8	28	80	◻◻

WLNFA050M
WLNFC050M
WLNFA075M
WLNFC075M
WLNFA100M
WLNFC100M
WLNFA125M
WLNFC125M

S series Heavier range

75	32	10	36	70	≡
75	32	10	36	70	◻◻
100	32	10	36	90	≡
100	32	10	36	90	◻◻
125	32	10	36	100	≡
125	32	10	36	100	◻◻
150	32	10	36	100	≡
150	32	10	36	100	◻◻

WLNFA075S
WLNFC075S
WLNFA100S
WLNFC100S
WLNFA125S
WLNFC125S
WLNFA150S
WLNFC150S

≡ Plain bearing
◻◻ Double ball bearing

mm

kg

NFA-T NFC-T

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate For M series 60x60mm (43x49 / 43x49mm)
For S series 90x70mm (65x45 / 75x55mm)



TSBK

TOP PLATE SWIVEL WITH BREAK




TF

TOP PLATE FIXED



TS

TOP PLATE SWIVEL



Mseries
Medium range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	==
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	==
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	==
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	==
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	==
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	==
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	==
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	==

Sseries
Heavier range

75	32	90X70	65X45/75X55	9	109	28	95	70	==
75	32	90X70	65X45/75X55	9	109	28	95	70	==
100	32	90X70	65X45/75X55	9	131,5	40	107	90	==
100	32	90X70	65X45/75X55	9	131,5	40	107	90	==
125	32	90X70	65X45/75X55	9	156,5	40	107	100	==
125	32	90X70	65X45/75X55	9	156,5	40	107	100	==
150	32	90X70	65X45/75X55	9	181,5	45	112	100	==
150	32	90X70	65X45/75X55	9	181,5	45	112	100	==

M050NFATS	M050NFATSBK	M050NFATF
M050NFCTS	M050NFCTSBK	M050NFCTF
M075NFATS	M075NFATSBK	M075NFATF
M075NFCTS	M075NFCTSBK	M075NFCTF
M100NFATS	M100NFATSBK	M100NFATF
M100NFCTS	M100NFCTSBK	M100NFCTF
M125NFATS	M125NFATSBK	M125NFATF
M125NFCTS	M125NFCTSBK	M125NFCTF


S075NFATS	S075NFATSBK	S075NFATF
S075NFCTS	S075NFCTSBK	S075NFCTF
S100NFATS	S100NFATSBK	S100NFATF
S100NFCTS	S100NFCTSBK	S100NFCTF
S125NFATS	S125NFATSBK	S125NFATF
S125NFCTS	S125NFCTSBK	S125NFCTF
S150NFATS	S150NFATSBK	S150NFATF
S150NFCTS	S150NFCTSBK	S150NFCTF

mm

kg

code

== Plain bearing
== Double ball bearing



support
type M-S

WHEEL SERIES NF

NFA-H NFC-H

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm



HSBK

HOLE FITTING SWIVEL WITH BREAK



HF

HOLE FITTING FIXED



HS

HOLE FITTING SWIVEL

										
50	24	10,2	73,5	25	77	50		M050NFAHS	M050NFAHSBK	M050NFAHF
50	24	10,2	73,5	25	77	50		M050NFCHS	M050NFCHSBK	M050NFCHF
75	24	10,2	101	30,5	86	60		M075NFAHS	M075NFAHSBK	M075NFAHF
75	24	10,2	101	30,5	86	60		M075NFCHS	M075NFCHSBK	M075NFCHF
100	24	10,2	123,5	40	101	70		M100NFAHS	M100NFAHSBK	M100NFAHF
100	24	10,2	123,5	40	101	70		M100NFCHS	M100NFCHSBK	M100NFCHF
125	24	10,2	148,5	43	104	80		M125NFAHS	M125NFAHSBK	M125NFAHF
125	24	10,2	148,5	43	104	80		M125NFCHS	M125NFCHSBK	M125NFCHF
75	32	12,2	109	28	95	70		S075NFAHS	S075NFAHSBK	S075NFAHF
75	32	12,2	109	28	95	70		S075NFCHS	S075NFCHSBK	S075NFCHF
100	32	12,2	131,5	40	107	90		S100NFAHS	S100NFAHSBK	S100NFAHF
100	32	12,2	131,5	40	107	90		S100NFCHS	S100NFCHSBK	S100NFCHF
125	32	12,2	156,5	40	107	100		S125NFAHS	S125NFAHSBK	S125NFAHF
125	32	12,2	156,5	40	107	100		S125NFCHS	S125NFCHSBK	S125NFCHF
150	32	12,2	181,5	45	112	100		S150NFAHS	S150NFAHSBK	S150NFAHF
150	32	12,2	181,5	45	112	100		S150NFCHS	S150NFCHSBK	S150NFCHF
mm							kg	code		

 Plain bearing
 Double ball bearing

NFA-B NFC-B



BSBK

BOLT STEM SWIVEL WITH BREAK



BS

BOLT STEM SWIVEL

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: For the M series, Bolt stem M10X20
For the S series, Bolt stem M12X25

Different bolt stems available
(M08X25, M10X30 etc)


									
50	24	M10X20	73,5	25	77	50		M050NFABS	M050NFABSBK
50	24	M10X20	73,5	25	77	50		M050NFCBS	M050NFCBSBK
75	24	M10X20	101	30,5	86	60		M075NFABS	M075NFABSBK
75	24	M10X20	101	30,5	86	60		M075NFCBS	M075NFCBSBK
100	24	M10X20	123,5	40	101	70		M100NFABS	M100NFABSBK
100	24	M10X20	123,5	40	101	70		M100NFCBS	M100NFCBSBK
125	24	M10X20	148,5	43	104	80		M125NFABS	M125NFABSBK
125	24	M10X20	148,5	43	104	80		M125NFCBS	M125NFCBSBK
75	32	M12X25	109	28	95	70		S075NFABS	S075NFABSBK
75	32	M12X25	109	28	95	70		S075NFCBS	S075NFCBSBK
100	32	M12X25	131,5	40	107	90		S100NFABS	S100NFABSBK
100	32	M12X25	131,5	40	107	90		S100NFCBS	S100NFCBSBK
125	32	M12X25	156,5	40	107	100		S125NFABS	S125NFABSBK
125	32	M12X25	156,5	40	107	100		S125NFCBS	S125NFCBSBK
150	32	M12X25	181,5	45	112	100		S150NFABS	S150NFABSBK
150	32	M12X25	181,5	45	112	100		S150NFCBS	S150NFCBSBK
mm							kg	code	

mm

kg

code

== Plain bearing
□□ Double ball bearing



support
type M-S


WHEEL
SERIES
NF



NFA / NFC

PLAIN BEARING

BALL BEARINGS



Properties

Resistance to chemicals

Resistance in wet conditions

Long service life

M series
Medium range

S series
Heavier range

50	24	8	28	50	≡
50	24	8	28	50	⊠
75	24	8	28	60	≡
75	24	8	28	60	⊠
100	24	8	28	70	≡
100	24	8	28	70	⊠
125	24	8	28	80	≡
125	24	8	28	80	⊠
75	32	10	36	70	≡
75	32	10	36	70	⊠
100	32	10	36	90	≡
100	32	10	36	90	⊠
125	32	10	36	100	≡
125	32	10	36	100	⊠
150	32	10	36	100	≡
150	32	10	36	100	⊠

mm

kg

WLNFA050M
WLNFC050M
WLNFA075M
WLNFC075M
WLNFA100M
WLNFC100M
WLNFA125M
WLNFC125M

WLNFA075S
WLNFC075S
WLNFA100S
WLNFC100S
WLNFA125S
WLNFC125S
WLNFA150S
WLNFC150S

≡ Plain bearing

⊠ Double ball bearing

NFA-T NFC-T

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate For M series 60x60mm (43x49 / 43x49mm)
For S series 90x70mm (65x45 / 75x55mm)

Threadguards: Steel




TSBKG
TOP PLATE SWIVEL
WITH BREAK AND TREAD GUARD



TFG
TOP PLATE FIXED
WITH TREAD GUARD



TSG
TOP PLATE SWIVEL
WITH TREAD GUARD



Mseries
Medium range

Sseries
Heavier range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	≡
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	⊠
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	≡
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	⊠
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	≡
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	⊠
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	≡
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	⊠
75	32	90X70	65X45/75X55	9	109	28	95	70	≡
75	32	90X70	65X45/75X55	9	109	28	95	70	⊠
100	32	90X70	65X45/75X55	9	131,5	40	107	90	≡
100	32	90X70	65X45/75X55	9	131,5	40	107	90	⊠
125	32	90X70	65X45/75X55	9	156,5	40	107	100	≡
125	32	90X70	65X45/75X55	9	156,5	40	107	100	⊠
150	32	90X70	65X45/75X55	9	181,5	45	112	100	≡
150	32	90X70	65X45/75X55	9	181,5	45	112	100	⊠

M050NFATSG	M050NFATSBKG	M050NFATFG
M050NFCTSG	M050NFCTSBKG	M050NFCTFG
M075NFATSG	M075NFATSBKG	M075NFATFG
M075NFCTSG	M075NFCTSBKG	M075NFCTFG
M100NFATSG	M100NFATSBKG	M100NFATFG
M100NFCTSG	M100NFCTSBKG	M100NFCTFG
M125NFATSG	M125NFATSBKG	M125NFATFG
M125NFCTSG	M125NFCTSBKG	M125NFCTFG


S075NFATSG	S075NFATSBKG	S075NFATFG
S075NFCTSG	S075NFCTSBKG	S075NFCTFG
S100NFATSG	S100NFATSBKG	S100NFATFG
S100NFCTSG	S100NFCTSBKG	S100NFCTFG
S125NFATSG	S125NFATSBKG	S125NFATFG
S125NFCTSG	S125NFCTSBKG	S125NFCTFG
S150NFATSG	S150NFATSBKG	S150NFATFG
S150NFCTSG	S150NFCTSBKG	S150NFCTFG

mm

kg

code

≡ Plain bearing
⊠ Double ball bearing



support
type **M-S**

WHEEL
SERIES
TP

NFA-H NFC-H

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm

Threadguards: Steel



HSBKKG

HOLE FITTING SWIVEL
WITH BREAK AND TREAD GUARD



HFG

HOLE FITTING FIXED
WITH TREAD GUARD



HSG

HOLE FITTING SWIVEL
WITH TREAD GUARD

										
50	24	10,2	73,5	25	77	50		M050NFAHSG	M050NFAHSBKG	M050NFAHFG
50	24	10,2	73,5	25	77	50		M050NFCHSG	M050NFCHSBKG	M050NFCHFG
75	24	10,2	101	30,5	86	60		M075NFAHSG	M075NFAHSBKG	M075NFAHFG
75	24	10,2	101	30,5	86	60		M075NFCHSG	M075NFCHSBKG	M075NFCHFG
100	24	10,2	123,5	40	101	70		M100NFAHSG	M100NFAHSBKG	M100NFAHFG
100	24	10,2	123,5	40	101	70		M100NFCHSG	M100NFCHSBKG	M100NFCHFG
125	24	10,2	148,5	43	104	80		M125NFAHSG	M125NFAHSBKG	M125NFAHFG
125	24	10,2	148,5	43	104	80		M125NFCHSG	M125NFCHSBKG	M125NFCHFG
75	32	12,2	109	28	95	70		S075NFAHSG	S075NFAHSBKG	S075NFAHFG
75	32	12,2	109	28	95	70		S075NFCHSG	S075NFCHSBKG	S075NFCHFG
100	32	12,2	131,5	40	107	90		S100NFAHSG	S100NFAHSBKG	S100NFAHFG
100	32	12,2	131,5	40	107	90		S100NFCHSG	S100NFCHSBKG	S100NFCHFG
125	32	12,2	156,5	40	107	100		S125NFAHSG	S125NFAHSBKG	S125NFAHFG
125	32	12,2	156,5	40	107	100		S125NFCHSG	S125NFCHSBKG	S125NFCHFG
150	32	12,2	181,5	45	112	100		S150NFAHSG	S150NFAHSBKG	S150NFAHFG
150	32	12,2	181,5	45	112	100		S150NFCHSG	S150NFCHSBKG	S150NFCHFG
mm							kg	code		

NFA-B NFC-B



BSBKKG
BOLT STEM SWIVEL
WITH BREAK AND TREAD GUARD



BSG
BOLT STEM SWIVEL
WITH TREAD GUARD

Support: Steel

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: For the M series, Bolt stem M10X20 | Different bolt stems available
For the S series, Bolt stem M12X25 (M08X25, M10X30 etc)

Threadguards: Steel


50	24	M10X20	73,5	25	77	50		M050NFABSG	M050NFABSBKG
50	24	M10X20	73,5	25	77	50		M050NFCBSG	M050NFCBSBKG
75	24	M10X20	101	30,5	86	60		M075NFABSG	M075NFABSBKG
75	24	M10X20	101	30,5	86	60		M075NFCBSG	M075NFCBSBKG
100	24	M10X20	123,5	40	101	70		M100NFABSG	M100NFABSBKG
100	24	M10X20	123,5	40	101	70		M100NFCBSG	M100NFCBSBKG
125	24	M10X20	148,5	43	104	80		M125NFABSG	M125NFABSBKG
125	24	M10X20	148,5	43	104	80		M125NFCBSG	M125NFCBSBKG
75	32	M12X25	109	28	95	70		S075NFABSG	S075NFABSBKG
75	32	M12X25	109	28	95	70		S075NFCBSG	S075NFCBSBKG
100	32	M12X25	131,5	40	107	90		S100NFABSG	S100NFABSBKG
100	32	M12X25	131,5	40	107	90		S100NFCBSG	S100NFCBSBKG
125	32	M12X25	156,5	40	107	100		S125NFABSG	S125NFABSBKG
125	32	M12X25	156,5	40	107	100		S125NFCBSG	S125NFCBSBKG
150	32	M12X25	181,5	45	112	100		S150NFABSG	S150NFABSBKG
150	32	M12X25	181,5	45	112	100		S150NFCBSG	S150NFCBSBKG

mm

kg

code

Plain bearing
 Double ball bearing



support
type **M-S**

WHEEL
SERIES
TP




NFA

PLAIN BEARING

NFC/NFX

BALL BEARINGS



Properties

Resistance to chemicals
Resistance in wet conditions
Long service life

M series

Medium range

50	24	8	28	50	≡
50	24	8	28	50	◻◻
75	24	8	28	60	≡
75	24	8	28	60	◻◻
100	24	8	28	70	≡
100	24	8	28	70	◻◻
125	24	8	28	80	≡
125	24	8	28	80	◻◻

WLNFA050M
WLNFC050M
WLNFA075M
WLNFC075M
WLNFA100M
WLNFC100M
WLNFA125M
WLNFC125M

S series

Heavier range

75	32	10	36	70	≡
75	32	10	36	70	◻◻
100	32	10	36	90	≡
100	32	10	36	90	◻◻
125	32	10	36	100	≡
125	32	10	36	100	◻◻
150	32	10	36	100	≡
150	32	10	36	100	◻◻

WLNFA075S
WLNFC075S
WLNFA100S
WLNFC100S
WLNFA125S
WLNFC125S
WLNFA150S
WLNFC150S

≡ Plain bearing
◻◻ Double ball bearing

mm

kg

STAINLESS STEEL

NFA-T NFC-T

Support: Stainless Steel (AISI 304)

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate For M series 60x60mm (43x49 / 43x49mm)
For S series 90x70mm (65x45 / 75x55mm)



TSBK

TOP PLATE SWIVEL WITH BREAK



TF

TOP PLATE FIXED



TS

TOP PLATE SWIVEL



M series
Medium range

S series
Heavier range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	—
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	□□
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	—
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	□□
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	—
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	□□
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	—
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	□□
75	32	90X70	65X45/75X55	9	109	28	95	70	—
75	32	90X70	65X45/75X55	9	109	28	95	70	□□
100	32	90X70	65X45/75X55	9	131,5	40	107	90	—
100	32	90X70	65X45/75X55	9	131,5	40	107	90	□□
125	32	90X70	65X45/75X55	9	156,5	40	107	100	—
125	32	90X70	65X45/75X55	9	156,5	40	107	100	□□
150	32	90X70	65X45/75X55	9	181,5	45	112	100	—
150	32	90X70	65X45/75X55	9	181,5	45	112	100	□□

mm

kg


MX050NFATS	MX050NFATSBK	MX050NFATF
MX050NFCTS	MX050NFCTSBK	MX050NFCTF
MX075NFATS	MX075NFATSBK	MX075NFATF
MX075NFCTS	MX075NFCTSBK	MX075NFCTF
MX100NFATS	MX100NFATSBK	MX100NFATF
MX100NFCTS	MX100NFCTSBK	MX100NFCTF
MX125NFATS	MX125NFATSBK	MX125NFATF
MX125NFCTS	MX125NFCTSBK	MX125NFCTF

SX075NFATS	SX075NFATSBK	SX075NFATF
SX075NFCTS	SX075NFCTSBK	SX075NFCTF
SX100NFATS	SX100NFATSBK	SX100NFATF
SX100NFCTS	SX100NFCTSBK	SX100NFCTF
SX125NFATS	SX125NFATSBK	SX125NFATF
SX125NFCTS	SX125NFCTSBK	SX125NFCTF
SX150NFATS	SX150NFATSBK	SX150NFATF
SX150NFCTS	SX150NFCTSBK	SX150NFCTF

code

— Plain bearing

□□ Double ball bearing



support
type

M-S

WHEEL SERIES

NF



Stainless Steel

Notice:

For castors with also stainless steel bearings, substitute the NFC part of the code with NFX

STAINLESS STEEL

NFA-H

NFC-H

Support: Stainless Steel (AISI 304)

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm



HSBK

HOLE FITTING SWIVEL WITH BREAK



HF

HOLE FITTING FIXED



HS

HOLE FITTING SWIVEL

										
50	24	10,2	73,5	25	77	50		MX050NFAHS	MX050NFAHSBK	MX050NFAHF
50	24	10,2	73,5	25	77	50		MX050NFCHS	MX050NFCHSBK	MX050NFCHF
75	24	10,2	101	30,5	86	60		MX075NFAHS	MX075NFAHSBK	MX075NFAHF
75	24	10,2	101	30,5	86	60		MX075NFCHS	MX075NFCHSBK	MX075NFCHF
100	24	10,2	123,5	40	101	70		MX100NFAHS	MX100NFAHSBK	MX100NFAHF
100	24	10,2	123,5	40	101	70		MX100NFCHS	MX100NFCHSBK	MX100NFCHF
125	24	10,2	148,5	43	104	80		MX125NFAHS	MX125NFAHSBK	MX125NFAHF
125	24	10,2	148,5	43	104	80		MX125NFCHS	MX125NFCHSBK	MX125NFCHF
75	32	12,2	109	28	95	70		SX075NFAHS	SX075NFAHSBK	SX075NFAHF
75	32	12,2	109	28	95	70		SX075NFCHS	SX075NFCHSBK	SX075NFCHF
100	32	12,2	131,5	40	107	90		SX100NFAHS	SX100NFAHSBK	SX100NFAHF
100	32	12,2	131,5	40	107	90		SX100NFCHS	SX100NFCHSBK	SX100NFCHF
125	32	12,2	156,5	40	107	100		SX125NFAHS	SX125NFAHSBK	SX125NFAHF
125	32	12,2	156,5	40	107	100		SX125NFCHS	SX125NFCHSBK	SX125NFCHF
150	32	12,2	181,5	45	112	100		SX150NFAHS	SX150NFAHSBK	SX150NFAHF
150	32	12,2	181,5	45	112	100		SX150NFCHS	SX150NFCHSBK	SX150NFCHF
mm							kg	code		

 Plain bearing

 Double ball bearing

Notice:

For castors with also stainless steel bearings, substitute the NFC part of the code with NFX

STAINLESS STEEL

NFA-B

NFC-B

Support: Stainless Steel (AISI 304)

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: For the M series, Bolt stem M10X20 | Different bolt stems available (M08X25, M10X30 etc)
For the S series, Bolt stem M12X25



BSBK

BOLT STEM SWIVEL WITH BREAK



BS

BOLT STEM SWIVEL

50	24	M10X20	73,5	25	77	50	≡
50	24	M10X20	73,5	25	77	50	⊠
75	24	M10X20	101	30,5	86	60	≡
75	24	M10X20	101	30,5	86	60	⊠
100	24	M10X20	123,5	40	101	70	≡
100	24	M10X20	123,5	40	101	70	⊠
125	24	M10X20	148,5	43	104	80	≡
125	24	M10X20	148,5	43	104	80	⊠
75	32	M12X25	109	28	95	70	≡
75	32	M12X25	109	28	95	70	⊠
100	32	M12X25	131,5	40	107	90	≡
100	32	M12X25	131,5	40	107	90	⊠
125	32	M12X25	156,5	40	107	100	≡
125	32	M12X25	156,5	40	107	100	⊠
150	32	M12X25	181,5	45	112	100	≡
150	32	M12X25	181,5	45	112	100	⊠

mm


kg

MX050NFABS	MX050NFABSBK
MX050NFCBS	MX050NFCBSBK
MX075NFABS	MX075NFABSBK
MX075NFCBS	MX075NFCBSBK
MX100NFABS	MX100NFABSBK
MX100NFCBS	MX100NFCBSBK
MX125NFABS	MX125NFABSBK
MX125NFCBS	MX125NFCBSBK
SX075NFABS	SX075NFABSBK
SX075NFCBS	SX075NFCBSBK
SX100NFABS	SX100NFABSBK
SX100NFCBS	SX100NFCBSBK
SX125NFABS	SX125NFABSBK
SX125NFCBS	SX125NFCBSBK
SX150NFABS	SX150NFABSBK
SX150NFCBS	SX150NFCBSBK

code

≡ Plain bearing

⊠ Double ball bearing



support type

M-S

WHEEL SERIES

NF



Stainless Steel

Notice:

For castors with also stainless steel bearings, substitute the NFC part of the code with NFX


WITH STAINLESS
THREAD GUARDS



NFA & NFC/NFX

PLAIN BEARING

BALL BEARINGS



Properties

Resistance to chemicals

Resistance in wet conditions

Long service life

Notice:

For castors with also stainless steel bearings,
substitute the NFC part of the code with NFX

 Plain bearing
 Double ball bearing

M series
Medium range

S series
Heavier range

50	24	8	28	50	
50	24	8	28	50	
75	24	8	28	60	
75	24	8	28	60	
100	24	8	28	70	
100	24	8	28	70	
125	24	8	28	80	
125	24	8	28	80	
75	32	10	36	70	
75	32	10	36	70	
100	32	10	36	90	
100	32	10	36	90	
125	32	10	36	100	
125	32	10	36	100	
150	32	10	36	100	
150	32	10	36	100	

mm

kg

WLNFA050M
 WLNFC050M
 WLNFA075M
 WLNFC075M
 WLNFA100M
 WLNFC100M
 WLNFA125M
 WLNFC125M

WLNFA075S
 WLNFC075S
 WLNFA100S
 WLNFC100S
 WLNFA125S
 WLNFC125S
 WLNFA150S
 WLNFC150S

STAINLESS STEEL

NFA-T NFC-T

Support: Stainless Steel (AISI 304)

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate For M series 60x60mm (43x49 / 43x49mm)
For S series 90x70mm (65x45 / 75x55mm)

Threadguards: Stainless Steel threadguards (AISI 304)



TSBKG

TOP PLATE SWIVEL
WITH BREAK AND TREAD GUARD




TFG

TOP PLATE FIXED
WITH TREAD GUARD



TSG

TOP PLATE SWIVEL
WITH TREAD GUARD



50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	■
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	■
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	■
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	■
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	■
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	■
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	■
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	■

75	32	90X70	65X45/75X55	9	109	28	95	70	■
75	32	90X70	65X45/75X55	9	109	28	95	70	■
100	32	90X70	65X45/75X55	9	131,5	40	107	90	■
100	32	90X70	65X45/75X55	9	131,5	40	107	90	■
125	32	90X70	65X45/75X55	9	156,5	40	107	100	■
125	32	90X70	65X45/75X55	9	156,5	40	107	100	■
150	32	90X70	65X45/75X55	9	181,5	45	112	100	■
150	32	90X70	65X45/75X55	9	181,5	45	112	100	■

MX050NFATSGX MX050NFATSBKGX MX050NFATFGX
MX050NFCTSGX MX050NFCTSBKGX MX050NFCTFGX
MX075NFATSGX MX075NFATSBKGX MX075NFATFGX
MX075NFCTSGX MX075NFCTSBKGX MX075NFCTFGX
MX100NFATSGX MX100NFATSBKGX MX100NFATFGX
MX100NFCTSGX MX100NFCTSBKGX MX100NFCTFGX
MX125NFATSGX MX125NFATSBKGX MX125NFATFGX
MX125NFCTSGX MX125NFCTSBKGX MX125NFCTFGX


SX075NFATSGX SX075NFATSBKGX SX075NFATFGX
SX075NFCTSGX SX075NFCTSBKGX SX075NFCTFGX
SX100NFATSGX SX100NFATSBKGX SX100NFATFGX
SX100NFCTSGX SX100NFCTSBKGX SX100NFCTFGX
SX125NFATSGX SX125NFATSBKGX SX125NFATFGX
SX125NFCTSGX SX125NFCTSBKGX SX125NFCTFGX
SX150NFATSGX SX150NFATSBKGX SX150NFATFGX
SX150NFCTSGX SX150NFCTSBKGX SX150NFCTFGX

kg

code

■ Plain bearing

■ Double ball bearing

support
type

M-S

WHEEL SERIES

NF

Notice:

For castors with also stainless steel bearings,
substitute the NFC part of the code with NFX

STAINLESS STEEL

NFA-H

NFC-H

Support: Stainless Steel (AISI 304)**Wheel:** White Polyamide (Nylon 6) with Fiber glass, 90shA**Axle material:** Plain bearing
Ball bearing**Type of fitting:** Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm**Threadguards:** Stainless Steel threadguards (AISI 304)

HSBKKG

HOLE FITTING SWIVEL
WITH BREAK AND TREAD GUARD

HFG

HOLE FITTING FIXED
WITH TREAD GUARD

HSG

HOLE FITTING SWIVEL
WITH TREAD GUARD

50	24	10,2	73,5	25	77	50	—
50	24	10,2	73,5	25	77	50	••
75	24	10,2	101	30,5	86	60	—
75	24	10,2	101	30,5	86	60	••
100	24	10,2	123,5	40	101	70	—
100	24	10,2	123,5	40	101	70	••
125	24	10,2	148,5	43	104	80	—
125	24	10,2	148,5	43	104	80	••
75	32	12,2	109	28	95	70	—
75	32	12,2	109	28	95	70	••
100	32	12,2	131,5	40	107	90	—
100	32	12,2	131,5	40	107	90	••
125	32	12,2	156,5	40	107	100	—
125	32	12,2	156,5	40	107	100	••
150	32	12,2	181,5	45	112	100	—
150	32	12,2	181,5	45	112	100	••

mm

kg

MX050NFAHSGX	MX050NFAHSBKGX	MX050NFAHFGX
MX050NFCHSGX	MX050NFCHSBKGX	MX050NFCHFGX
MX075NFAHSGX	MX075NFAHSBKGX	MX075NFAHFGX
MX075NFCHSGX	MX075NFCHSBKGX	MX075NFCHFGX
MX100NFAHSGX	MX100NFAHSBKGX	MX100NFAHFGX
MX100NFCHSGX	MX100NFCHSBKGX	MX100NFCHFGX
MX125NFAHSGX	MX125NFAHSBKGX	MX125NFAHFGX
MX125NFCHSGX	MX125NFCHSBKGX	MX125NFCHFGX
SX075NFAHSGX	SX075NFAHSBKGX	SX075NFAHFGX
SX075NFCHSGX	SX075NFCHSBKGX	SX075NFCHFGX
SX100NFAHSGX	SX100NFAHSBKGX	SX100NFAHFGX
SX100NFCHSGX	SX100NFCHSBKGX	SX100NFCHFGX
SX125NFAHSGX	SX125NFAHSBKGX	SX125NFAHFGX
SX125NFCHSGX	SX125NFCHSBKGX	SX125NFCHFGX
SX150NFAHSGX	SX150NFAHSBKGX	SX150NFAHFGX
SX150NFCHSGX	SX150NFCHSBKGX	SX150NFCHFGX

code

— Plain bearing

•• Double ball bearing



Stainless Steel

Notice:

For castors with also stainless steel bearings, substitute the NFC part of the code with NFX

STAINLESS STEEL

NFA-B

NFC-B

Support: Stainless Steel (AISI 304)

Wheel: White Polyamide (Nylon 6) with Fiber glass, 90shA

Axle material: Plain bearing
Ball bearing

Type of fitting: For the M series, Bolt stem M10X20 | Different bolt stems available (M08X25, M10X30 etc)
For the S series, Bolt stem M12X25

Threadguards: Stainless Steel threadguards (AISI 304)



BSBKG

BOLT STEM SWIVEL
WITH BREAK AND TREAD GUARD



BSG

BOLT STEM SWIVEL
WITH TREAD GUARD


50	24	M10X20	73,5	25	77	50		MX050NFABSGX	MX050NFABSBKGX
50	24	M10X20	73,5	25	77	50		MX050NFCBSGX	MX050NFCBSBKGX
75	24	M10X20	101	30,5	86	60		MX075NFABSGX	MX075NFABSBKGX
75	24	M10X20	101	30,5	86	60		MX075NFCBSGX	MX075NFCBSBKGX
100	24	M10X20	123,5	40	101	70		MX100NFABSGX	MX100NFABSBKGX
100	24	M10X20	123,5	40	101	70		MX100NFCBSGX	MX100NFCBSBKGX
125	24	M10X20	148,5	43	104	80		MX125NFABSGX	MX125NFABSBKGX
125	24	M10X20	148,5	43	104	80		MX125NFCBSGX	MX125NFCBSBKGX
75	32	M12X25	109	28	95	70		SX075NFABSGX	SX075NFABSBKGX
75	32	M12X25	109	28	95	70		SX075NFCBSGX	SX075NFCBSBKGX
100	32	M12X25	131,5	40	107	90		SX100NFABSGX	SX100NFABSBKGX
100	32	M12X25	131,5	40	107	90		SX100NFCBSGX	SX100NFCBSBKGX
125	32	M12X25	156,5	40	107	100		SX125NFABSGX	SX125NFABSBKGX
125	32	M12X25	156,5	40	107	100		SX125NFCBSGX	SX125NFCBSBKGX
150	32	M12X25	181,5	45	112	100		SX150NFABSGX	SX150NFABSBKGX
150	32	M12X25	181,5	45	112	100		SX150NFCBSGX	SX150NFCBSBKGX

mm

kg

code

Plain bearing
 Double ball bearing

support
type

M-S

WHEEL SERIES

NF



Stainless Steel

Notice:

For castors with also stainless steel bearings, substitute the NFC part of the code with NFX