

WHEEL SERIES

TP

TPA

- Thermoplastic grey rubber
- Plain bearing

TPC

- Thermoplastic grey rubber
- Double ball bearing

TPS

- Thermoplastic grey rubber
- Precision bearing

General technical characteristics

Wheel material	Thermoplastic grey non marking rubber
Type of bearing:	Plain bearing Ball bearing
Center:	Polypropylene
Thermal range	-15C / + 80C
Thread hardness:	82shA




We serve the needs of the application

www.rodasa.com



TPA
PLAIN BEARING

TPC
BALL BEARINGS



Properties

Resistance to chemicals
Resistance in wet conditions
Long service life

M series Medium range

50	24	8	28	50	≡
50	24	8	29	50	◻◻
75	24	8	28	60	≡
75	24	8	28	60	◻◻
100	24	8	28	70	≡
100	24	8	29	70	◻◻
125	24	8	28	80	≡
125	24	8	28	80	◻◻

WLTPA050M
WLTPC050M
WLTPA075M
WLTPC075M
WLTPA100M
WLTPC100M
WLTPA125M
WLTPC125M

S series Heavier range

75	32	10	36	70	≡
75	32	10	36	70	◻◻
100	32	10	36	90	≡
100	32	10	36	90	◻◻
125	32	10	36	100	≡
125	32	10	36	100	◻◻
150	32	10	36	100	≡
150	32	10	36	100	◻◻

WLTPA075S
WLTPC075S
WLTPA100S
WLTPC100S
WLTPA125S
WLTPC125S
WLTPA150S
WLTPC150S

≡ Plain bearing
◻◻ Double ball bearing

mm

kg

TPA-T TPC-T

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate for M series 60x60mm (43x49 / 43x49mm)
for S series 90x70mm (65x45 / 75x55mm)



TSBK

TOP PLATE SWIVEL WITH BREAK



TF

TOP PLATE FIXED



TS

TOP PLATE SWIVEL



M series
Medium range

S series
Heavier range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	≡
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	⊠
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	≡
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	⊠
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	≡
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	⊠
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	≡
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	⊠
75	32	90X70	65X45/75X55	9	109	28	95	70	≡
75	32	90X70	65X45/75X55	9	109	28	95	70	⊠
100	32	90X70	65X45/75X55	9	131,5	40	107	90	≡
100	32	90X70	65X45/75X55	9	131,5	40	107	90	⊠
125	32	90X70	65X45/75X55	9	156,5	40	107	100	≡
125	32	90X70	65X45/75X55	9	156,5	40	107	100	⊠
150	32	90X70	65X45/75X55	9	181,5	45	112	100	≡
150	32	90X70	65X45/75X55	9	181,5	45	112	100	⊠


M050TPATS	M050TPATSBK	M050TPATF
M050TPCTS	M050TPCTSBK	M050TPCTF
M075TPATS	M075TPATSBK	M075TPATF
M075TPCTS	M075TPCTSBK	M075TPCTF
M100TPATS	M100TPATSBK	M100TPATF
M100TPCTS	M100TPCTSBK	M100TPCTF
M125TPATS	M125TPATSBK	M125TPATF
M125TPCTS	M125TPCTSBK	M125TPCTF
S075TPATS	S075TPATSBK	S075TPATF
S075TPCTS	S075TPCTSBK	S075TPCTF
S100TPATS	S100TPATSBK	S100TPATF
S100TPCTS	S100TPCTSBK	S100TPCTF
S125TPATS	S125TPATSBK	S125TPATF
S125TPCTS	S125TPCTSBK	S125TPCTF
S150TPATS	S150TPATSBK	S150TPATF
S150TPCTS	S150TPCTSBK	S150TPCTF

mm

kg

code

≡ Plain bearing
⊠ Double ball bearing



support
type

M-S

WHEEL
SERIES
TP

TPA-H TPC-H

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm



HSBK

HOLE FITTING SWIVEL WITH BREAK



HF

HOLE FITTING FIXED



HS

HOLE FITTING SWIVEL

										
50	24	10,2	73,5	25	77	50		M050TPAHS	M050TPAHSBK	M050TPAHF
50	24	10,2	73,5	25	77	50		M050TPCHS	M050TPCHSBK	M050TPCHF
75	24	10,2	101	30,5	86	60		M075TPAHS	M075TPAHSBK	M075TPAHF
75	24	10,2	101	30,5	86	60		M075TPCHS	M075TPCHSBK	M075TPCHF
100	24	10,2	123,5	40	101	70		M100TPAHS	M100TPAHSBK	M100TPAHF
100	24	10,2	123,5	40	101	70		M100TPCHS	M100TPCHSBK	M100TPCHF
125	24	10,2	148,5	43	104	80		M125TPAHS	M125TPAHSBK	M125TPAHF
125	24	10,2	148,5	43	104	80		M125TPCHS	M125TPCHSBK	M125TPCHF
75	32	12,2	109	28	95	70		S075TPAHS	S075TPAHSBK	S075TPAHF
75	32	12,2	109	28	95	70		S075TPCHS	S075TPCHSBK	S075TPCHF
100	32	12,2	131,5	40	107	90		S100TPAHS	S100TPAHSBK	S100TPAHF
100	32	12,2	131,5	40	107	90		S100TPCHS	S100TPCHSBK	S100TPCHF
125	32	12,2	156,5	40	107	100		S125TPAHS	S125TPAHSBK	S125TPAHF
125	32	12,2	156,5	40	107	100		S125TPCHS	S125TPCHSBK	S125TPCHF
150	32	12,2	181,5	45	112	100		S150TPAHS	S150TPAHSBK	S150TPAHF
150	32	12,2	181,5	45	112	100		S150TPCHS	S150TPCHSBK	S150TPCHF
mm							kg	code		

 Plain bearing
 Double ball bearing

TPA-B TPC-B

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: for the M series, Bolt stem M10X20 | Different bolt stems available
for the S series, Bolt stem M12X25 | (M08X25, M10X30 etc)



BSBK

BOLT STEM SWIVEL WITH BREAK



BS

BOLT STEM SWIVEL

							
50	24	M10X20	73,5	25	77	50	
50	24	M10X20	73,5	25	77	50	
75	24	M10X20	101	30,5	86	60	
75	24	M10X20	101	30,5	86	60	
100	24	M10X20	123,5	40	101	70	
100	24	M10X20	123,5	40	101	70	
125	24	M10X20	148,5	43	104	80	
125	24	M10X20	148,5	43	104	80	
75	32	M12X25	109	28	95	70	
75	32	M12X25	109	28	95	70	
100	32	M12X25	131,5	40	107	90	
100	32	M12X25	131,5	40	107	90	
125	32	M12X25	156,5	40	107	100	
125	32	M12X25	156,5	40	107	100	
150	32	M12X25	181,5	45	112	100	
150	32	M12X25	181,5	45	112	100	


mm

kg

M050TPABS	M050TPABSBK
M050TPCBS	M050TPCBSBK
M075TPABS	M075TPABSBK
M075TPCBS	M075TPCBSBK
M100TPABS	M100TPABSBK
M100TPCBS	M100TPCBSBK
M125TPABS	M125TPABSBK
M125TPCBS	M125TPCBSBK
S075TPABS	S075TPABSBK
S075TPCBS	S075TPCBSBK
S100TPABS	S100TPABSBK
S100TPCBS	S100TPCBSBK
S125TPABS	S125TPABSBK
S125TPCBS	S125TPCBSBK
S150TPABS	S150TPABSBK
S150TPCBS	S150TPCBSBK

code

≡ Plain bearing
⊠ Double ball bearing



support
type M-S

WHEEL
SERIES
TP

M series
Medium range

S series
Heavier range

TPA-EQ TPA-ER TPC-EQ TPC-ER

Support: Steel

Wheel: Grey rubber non marking, 82shA
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Expander square for tubes 21/24mm, 24/27mm, 27/31mm, 31/35mm, 35/40mm
Expander round for tubes 19/23mm, 23/26mm, 26/30mm

ERSBK
EXPANDER ROUND WITH BREAK

EQSBK
EXPANDER SQUARE WITH BREAK

EQS
EXPANDER SQUARE

ERS
EXPANDER ROUND

						
50	24	73.5	25	77	50	
50	24	73.5	25	77	50	
75	24	101	30.5	86	60	
75	24	101	30.5	86	60	
100	24	123.5	40	101	70	
100	24	123.5	40	101	70	
125	24	148.5	43	104	80	
125	24	148.5	43	104	80	
75	32	109	28	95	70	
75	32	109	28	95	70	
100	32	131.5	40	107	90	
100	32	131.5	40	107	90	
125	32	156.5	40	107	100	
125	32	156.5	40	107	100	
150	32	181.5	45	112	100	
150	32	181.5	45	112	100	
mm					kg	

			
M050TPAEQS()	M050TPAEQS()BK	M050TPAERS()	M050TPAERS()BK
M050TPCEQS()	M050TPCEQS()BK	M050TPCERS()	M050TPCERS()BK
M075TPAEQS()	M075TPAEQS()BK	M075TPAERS()	M075TPAERS()BK
M075TPCEQS()	M075TPCEQS()BK	M075TPCERS()	M075TPCERS()BK
M100TPAEQS()	M100TPAEQS()BK	M100TPAERS()	M100TPAERS()BK
M100TPCEQS()	M100TPCEQS()BK	M100TPCERS()	M100TPCERS()BK
M125TPAEQS()	M125TPAEQS()BK	M125TPAERS()	M125TPAERS()BK
M125TPCEQS()	M125TPCEQS()BK	M125TPCERS()	M125TPCERS()BK
S075TPAEQS()	S075TPAEQS()BK	S075TPAERS()	S075TPAERS()BK
S075TPCEQS()	S075TPCEQS()BK	S075TPCERS()	S075TPCERS()BK
S100TPAEQS()	S100TPAEQS()BK	S100TPAERS()	S100TPAERS()BK
S100TPCEQS()	S100TPCEQS()BK	S100TPCERS()	S100TPCERS()BK
S125TPAEQS()	S125TPAEQS()BK	S125TPAERS()	S125TPAERS()BK
S125TPCEQS()	S125TPCEQS()BK	S125TPCERS()	S125TPCERS()BK
S150TPAEQS()	S150TPAEQS()BK	S150TPAERS()	S150TPAERS()BK
S150TPCEQS()	S150TPCEQS()BK	S150TPCERS()	S150TPCERS()BK
			code

 Plain bearing
 Double ball bearing

Notice:

To get the complete article Nr, just fill in the bracket the requested dimension e.g for Square expander for tube 21/24mm, the article Nr is **M050TPAEQS(21/24)** while for round expander for tube 23/26mm, the article Nr is **M050TPAERS(23/26)**

WITH METAL
THREAD GUARDS



TPA-G / TPC-G

PLAIN BEARING

BALL BEARINGS



Properties

Resistance to chemicals
Resistance in wet conditions
Long service life

Notes

For stainless steel bearings you have to switch the TPC part of the code to TPX

 Plain bearing
 Double ball bearing

M series
Medium range

S series
Heavier range

50	24	8	28	50	
50	24	8	28	50	
75	24	8	28	60	
75	24	8	28	60	
100	24	8	28	70	
100	24	8	28	70	
125	24	8	28	80	
125	24	8	28	80	
75	32	10	36	70	
75	32	10	36	70	
100	32	10	36	90	
100	32	10	36	90	
125	32	10	36	100	
125	32	10	36	100	
150	32	10	36	100	
150	32	10	36	100	

mm

kg

WLTPA050M
WLTPC050M
WLTPA075M
WLTPC075M
WLTPA100M
WLTPC100M
WLTPA125M
WLTPC125M
WLTPA075S
WLTPC075S
WLTPA100S
WLTPC100S
WLTPA125S
WLTPC125S
WLTPA150S
WLTPC150S

TPA-T TPC-T



TSBKG
TOP PLATE SWIVEL WITH BREAK
AND TREAD GUARD



TFG
TOP PLATE FIXED
WITH TREAD GUARD



TSG
TOP PLATE SWIVEL
WITH TREAD GUARD

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate For M series 60x60mm (43x49 / 43x49mm)
For S series 90x70mm (65x45 / 75x55mm)

Threadguards: Steel threadguards



M series
Medium range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	≡
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	□□
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	≡
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	□□
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	≡
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	□□
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	≡
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	□□

S series
Heavier range

75	32	90X70	65X45/75X55	9	109	28	95	70	≡
75	32	90X70	65X45/75X55	9	109	28	95	70	□□
100	32	90X70	65X45/75X55	9	131,5	40	107	90	≡
100	32	90X70	65X45/75X55	9	131,5	40	107	90	□□
125	32	90X70	65X45/75X55	9	156,5	40	107	100	≡
125	32	90X70	65X45/75X55	9	156,5	40	107	100	□□
150	32	90X70	65X45/75X55	9	181,5	45	112	100	≡
150	32	90X70	65X45/75X55	9	181,5	45	112	100	□□

M050TPATSG	M050TPATSBKG	M050TPATFG
M050TPCTSG	M050TPCTSBKG	M050TPCTFG
M075TPATSG	M075TPATSBKG	M075TPATFG
M075TPCTSG	M075TPCTSBKG	M075TPCTFG
M100TPATSG	M100TPATSBKG	M100TPATFG
M100TPCTSG	M100TPCTSBKG	M100TPCTFG
M125TPATSG	M125TPATSBKG	M125TPATFG
M125TPCTSG	M125TPCTSBKG	M125TPCTFG


S075TPATSG	S075TPATSBKG	S075TPATFG
S075TPCTSG	S075TPCTSBKG	S075TPCTFG
S100TPATSG	S100TPATSBKG	S100TPATFG
S100TPCTSG	S100TPCTSBKG	S100TPCTFG
S125TPATSG	S125TPATSBKG	S125TPATFG
S125TPCTSG	S125TPCTSBKG	S125TPCTFG
S150TPATSG	S150TPATSBKG	S150TPATFG
S150TPCTSG	S150TPCTSBKG	S150TPCTFG

mm

kg

code

≡ Plain bearing
□□ Double ball bearing



support type **M-S**

WHEEL
SERIES
TP

TPA-H TPC-H

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm

Threadguards: Steel threadguards



HSBKG
HOLE FITTING SWIVEL WITH BREAK
AND TREAD GUARD



HFG
HOLE FITTING FIXED
WITH TREAD GUARD



HSG
HOLE FITTING SWIVEL
WITH TREAD GUARD

										
50	24	10.2	73.5	25	77	50		M050TPAHSG	M050TPAHSBKG	M050TPAHFG
50	24	10.2	73.5	25	77	50		M050TPCHSG	M050TPCHSBKG	M050TPCHFG
75	24	10.2	101	30.5	86	60		M075TPAHSG	M075TPAHSBKG	M075TPAHFG
75	24	10.2	101	30.5	86	60		M075TPCHSG	M075TPCHSBKG	M075TPCHFG
100	24	10.2	123.5	40	101	70		M100TPAHSG	M100TPAHSBKG	M100TPAHFG
100	24	10.2	123.5	40	101	70		M100TPCHSG	M100TPCHSBKG	M100TPCHFG
125	24	10.2	148.5	43	104	80		M125TPAHSG	M125TPAHSBKG	M125TPAHFG
125	24	10.2	148.5	43	104	80		M125TPCHSG	M125TPCHSBKG	M125TPCHFG
75	32	12.2	109	28	95	70		S075TPAHSG	S075TPAHSBKG	S075TPAHFG
75	32	12.2	109	28	95	70		S075TPCHSG	S075TPCHSBKG	S075TPCHFG
100	32	12.2	131.5	40	107	90		S100TPAHSG	S100TPAHSBKG	S100TPAHFG
100	32	12.2	131.5	40	107	90		S100TPCHSG	S100TPCHSBKG	S100TPCHFG
125	32	12.2	156.5	40	107	100		S125TPAHSG	S125TPAHSBKG	S125TPAHFG
125	32	12.2	156.5	40	107	100		S125TPCHSG	S125TPCHSBKG	S125TPCHFG
150	32	12.2	181.5	45	112	100		S150TPAHSG	S150TPAHSBKG	S150TPAHFG
150	32	12.2	181.5	45	112	100		S150TPCHSG	S150TPCHSBKG	S150TPCHFG
mm							kg	code		

 Plain bearing
 Double ball bearing

TPA-B TPC-B



BSBKKG
BOLT STEM SWIVEL WITH BREAK
AND TREAD GUARD



BSG
BOLT STEM SWIVEL
WITH TREAD GUARD


Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: For the M series, Bolt stem M10X20 | Different bolt stems available
For the S series, Bolt stem M12X25 | (M08X25, M10X30 etc)

Threadguards: Steel thread guards



M series
Medium range

S series
Heavier range

50	24	M10X20	73.5	25	77	50	■
50	24	M10X20	73.5	25	77	50	■
75	24	M10X20	101	30.5	86	60	■
75	24	M10X20	101	30.5	86	60	■
100	24	M10X20	123.5	40	101	70	■
100	24	M10X20	123.5	40	101	70	■
125	24	M10X20	148.5	43	104	80	■
125	24	M10X20	148.5	43	104	80	■
75	32	M12X25	109	28	95	70	■
75	32	M12X25	109	28	95	70	■
100	32	M12X25	131.5	40	107	90	■
100	32	M12X25	131.5	40	107	90	■
125	32	M12X25	156.5	40	107	100	■
125	32	M12X25	156.5	40	107	100	■
150	32	M12X25	181.5	45	112	100	■
150	32	M12X25	181.5	45	112	100	■


mm

kg

M050TPABSG	M050TPABSBKG
M050TPCB SG	M050TPCB SBKG
M075TPABSG	M075TPABSBKG
M075TPCB SG	M075TPCB SBKG
M100TPABSG	M100TPABSBKG
M100TPCB SG	M100TPCB SBKG
M125TPABSG	M125TPABSBKG
M125TPCB SG	M125TPCB SBKG
S075TPABSG	S075TPABSBKG
S075TPCB SG	S075TPCB SBKG
S100TPABSG	S100TPABSBKG
S100TPCB SG	S100TPCB SBKG
S125TPABSG	S125TPABSBKG
S125TPCB SG	S125TPCB SBKG
S150TPABSG	S150TPABSBKG
S150TPCB SG	S150TPCB SBKG

code

■ Plain bearing
■ Double ball bearing



support
type **M-S**

WHEEL
SERIES
TP

TPA-EQ TPA-ER TPC-EQ TPC-ER

Support: Steel

Wheel: Grey rubber non marking, 82shA
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Expander square for tubes 21/24mm, 24/27mm, 27/31mm, 31/35mm, 35/40mm
Expander round for tubes 19/23mm, 23/26mm, 26/30mm

Threadguards: Steel thread guards

ERSBKG

EXPANDER ROUND
WITH BREAK AND TREAD GUARD



EQSBKG

EXPANDER SQUARE WITH BREAK
AND TREAD GUARD




ERSBKG

EXPANDER ROUND WITH BREAK
AND TREAD GUARD

EQSBKG

EXPANDER SQUARE
WITH BREAK AND TREAD GUARD



50	24	73.5	25	77	50	TPA
50	24	73.5	25	77	50	TPC
75	24	101	30.5	86	60	TPA
75	24	101	30.5	86	60	TPC
100	24	123.5	40	101	70	TPA
100	24	123.5	40	101	70	TPC
125	24	148.5	43	104	80	TPA
125	24	148.5	43	104	80	TPC

75	32	109	28	95	70	TPA
75	32	109	28	95	70	TPC
100	32	131.5	40	107	90	TPA
100	32	131.5	40	107	90	TPC
125	32	156.5	40	107	100	TPA
125	32	156.5	40	107	100	TPC
150	32	181.5	45	112	100	TPA
150	32	181.5	45	112	100	TPC

mm

kg



M050TPAEQS()G	M050TPAEQS()BKG	M050TPAERS()G	M050TPAERS()BKG
M050TPCEQS()G	M050TPCEQS()BKG	M050TPCERS()G	M050TPCERS()BKG
M075TPAEQS()G	M075TPAEQS()BKG	M075TPAERS()G	M075TPAERS()BKG
M075TPCEQS()G	M075TPCEQS()BKG	M075TPCERS()G	M075TPCERS()BKG
M100TPAEQS()G	M100TPAEQS()BKG	M100TPAERS()G	M100TPAERS()BKG
M100TPCEQS()G	M100TPCEQS()BKG	M100TPCERS()G	M100TPCERS()BKG
M125TPAEQS()G	M125TPAEQS()BKG	M125TPAERS()G	M125TPAERS()BKG
M125TPCEQS()G	M125TPCEQS()BKG	M125TPCERS()G	M125TPCERS()BKG

S075TPAEQS()G	S075TPAEQS()BKG	S075TPAERS()G	S075TPAERS()BKG
S075TPCEQS()G	S075TPCEQS()BKG	S075TPCERS()G	S075TPCERS()BKG
S100TPAEQS()G	S100TPAEQS()BKG	S100TPAERS()G	S100TPAERS()BKG
S100TPCEQS()G	S100TPCEQS()BKG	S100TPCERS()G	S100TPCERS()BKG
S125TPAEQS()G	S125TPAEQS()BKG	S125TPAERS()G	S125TPAERS()BKG
S125TPCEQS()G	S125TPCEQS()BKG	S125TPCERS()G	S125TPCERS()BKG
S150TPAEQS()G	S150TPAEQS()BKG	S150TPAERS()G	S150TPAERS()BKG
S150TPCEQS()G	S150TPCEQS()BKG	S150TPCERS()G	S150TPCERS()BKG

code

Notice:


To get the complete article Nr, just fill in the bracket the requested dimension e.g for Square expander for tube 21/24mm, the article Nr is **M050TPAEQS(21/24)G** while for round expander for tube 23/26mm, the article Nr is **M050TPAERS(23/26)G**

WITH PLASTIC
THREAD GUARDS



TPA-GP / TPS-GP

PLAIN BEARING SINGLE PRECISION BEARING



Properties

Resistance to chemicals
Resistance in wet conditions
Long service life

M series
Medium range

50	24	8	28	50	≡
50	24	8	28	50	□□
75	24	8	28	60	≡
75	24	8	28	60	□□
100	24	8	28	70	≡
100	24	8	28	70	□□
125	24	8	28	80	≡
125	24	8	28	80	□□

WLTPA050MGP
WLTPS050MGP
WLTPA075MGP
WLTPS075MGP
WLTPA100MGP
WLTPS100MGP
WLTPA125MGP
WLTPS125MGP

S series
Heavier range

75	32	10	36	70	≡
75	32	10	36	70	□□
100	32	10	36	90	≡
100	32	10	36	90	□□
125	32	10	36	100	≡
125	32	10	36	100	□□
150	32	10	36	100	≡
150	32	10	36	100	□□

WLTPA075SGP
WLTPS075SGP
WLTPA100SGP
WLTPS100SGP
WLTPA125SGP
WLTPS125SGP
WLTPA150SGP
WLTPS150SGP

≡ Plain bearing
□□ single precision bearing

mm

kg

TPA-T TPS-T



TSBKGP
TOP PLATE SWIVEL WITH BREAK



TFGP
TOP PLATE FIXED



TSGP
TOP PLATE SWIVEL

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate for M series 60x60mm (43x49 / 43x49mm)
for S series 90x70mm (65x45 / 75x55mm)

Threadguards: Plastic threadguards



M series
Medium range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	≡
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	□
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	≡
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	□
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	≡
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	□
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	≡
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	□

S series
Heavier range

75	32	90X70	65X45/75X55	9	109	28	95	70	≡
75	32	90X70	65X45/75X55	9	109	28	95	70	□
100	32	90X70	65X45/75X55	9	131,5	40	107	90	≡
100	32	90X70	65X45/75X55	9	131,5	40	107	90	□
125	32	90X70	65X45/75X55	9	156,5	40	107	100	≡
125	32	90X70	65X45/75X55	9	156,5	40	107	100	□
150	32	90X70	65X45/75X55	9	181,5	45	112	100	≡
150	32	90X70	65X45/75X55	9	181,5	45	112	100	□

M050TPATSGP	M050TPATSBKGP	M050TPATFGP
M050TPSTSGP	M050TPSTSBKGP	M050TPSTFGP
M075TPATSGP	M075TPATSBKGP	M075TPATFGP
M075TPSTSGP	M075TPSTSBKGP	M075TPSTFGP
M100TPATSGP	M100TPATSBKGP	M100TPATFGP
M100TPSTSGP	M100TPSTSBKGP	M100TPSTFGP
M125TPATSGP	M125TPATSBKGP	M125TPATFGP
M125TPSTSGP	M125TPSTSBKGP	M125TPSTFGP


S075TPATSGP	S075TPATSBKGP	S075TPATFGP
S075TPSTSGP	S075TPSTSBKGP	S075TPSTFGP
S100TPATSGP	S100TPATSBKGP	S100TPATFGP
S100TPSTSGP	S100TPSTSBKGP	S100TPSTFGP
S125TPATSGP	S125TPATSBKGP	S125TPATFGP
S125TPSTSGP	S125TPSTSBKGP	S125TPSTFGP
S150TPATSGP	S150TPATSBKGP	S150TPATFGP
S150TPSTSGP	S150TPSTSBKGP	S150TPSTFGP

mm

kg

code

≡ Plain bearing
□ Single precision bearing



support
type **M-S**

WHEEL
SERIES
TP

TPA-H TPS-H

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm

Threadguards: Plastic threadguards



HSBKGP
HOLE FITTING SWIVEL WITH BREAK



HFGRP
HOLE FITTING FIXED



HSGP
HOLE FITTING SWIVEL

50	24	10.2	73.5	25	77	50		M050TPAHSGP	M050TPAHSBKGP	M050TPAHFGP
50	24	10.2	73.5	25	77	50		M050TPSHSGP	M050TPSHSBKGP	M050TPSHFGP
75	24	10.2	101	30.5	86	60		M075TPAHSGP	M075TPAHSBKGP	M075TPAHFGP
75	24	10.2	101	30.5	86	60		M075TPSHSGP	M075TPSHSBKGP	M075TPSHFGP
100	24	10.2	123.5	40	101	70		M100TPAHSGP	M100TPAHSBKGP	M100TPAHFGP
100	24	10.2	123.5	40	101	70		M100TPSHSGP	M100TPSHSBKGP	M100TPSHFGP
125	24	10.2	148.5	43	104	80		M125TPAHSGP	M125TPAHSBKGP	M125TPAHFGP
125	24	10.2	148.5	43	104	80		M125TPSHSGP	M125TPSHSBKGP	M125TPSHFGP
75	32	12.2	109	28	95	70		S075TPAHSGP	S075TPAHSBKGP	S075TPAHFGP
75	32	12.2	109	28	95	70		S075TPSHSGP	S075TPSHSBKGP	S075TPSHFGP
100	32	12.2	131.5	40	107	90		S100TPAHSGP	S100TPAHSBKGP	S100TPAHFGP
100	32	12.2	131.5	40	107	90		S100TPSHSGP	S100TPSHSBKGP	S100TPSHFGP
125	32	12.2	156.5	40	107	100		S125TPAHSGP	S125TPAHSBKGP	S125TPAHFGP
125	32	12.2	156.5	40	107	100		S125TPSHSGP	S125TPSHSBKGP	S125TPSHFGP
150	32	12.2	181.5	45	112	100		S150TPAHSGP	S150TPAHSBKGP	S150TPAHFGP
150	32	12.2	181.5	45	112	100		S150TPSHSGP	S150TPSHSBKGP	S150TPSHFGP
mm							kg	code		

Plain bearing
 Single precision bearing

TPA-B TPS-B

Support: Steel

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: for the M series, Bolt stem M10X20 | Different bolt stems available
for the S series, Bolt stem M12X25 | (M08X25, M10X30 etc)


Threadguards: Plastic threadguards



BSBKGP
BOLT STEM SWIVEL WITH BREAK



BSGP
BOLT STEM SWIVEL



Mseries
Medium range

Sseries
Heavier range

50	24	M10X20	73,5	25	77	50	≡
50	24	M10X20	73,5	25	77	50	□◻
75	24	M10X20	101	30,5	86	60	≡
75	24	M10X20	101	30,5	86	60	□◻
100	24	M10X20	123,5	40	101	70	≡
100	24	M10X20	123,5	40	101	70	□◻
125	24	M10X20	148,5	43	104	80	≡
125	24	M10X20	148,5	43	104	80	□◻
75	32	M12X25	109	28	95	70	≡
75	32	M12X25	109	28	95	70	□◻
100	32	M12X25	131,5	40	107	90	≡
100	32	M12X25	131,5	40	107	90	□◻
125	32	M12X25	156,5	40	107	100	≡
125	32	M12X25	156,5	40	107	100	□◻
150	32	M12X25	181,5	45	112	100	≡
150	32	M12X25	181,5	45	112	100	□◻


mm

kg

M050TPABSGP	M050TPABSBKGP
M050TPSBSGP	M050TPSBSBKGP
M075TPABSGP	M075TPABSBKGP
M075TPSBSGP	M075TPSBSBKGP
M100TPABSGP	M100TPABSBKGP
M100TPSBSGP	M100TPSBSBKGP
M125TPABSGP	M125TPABSBKGP
M125TPSBSGP	M125TPSBSBKGP
S075TPABSGP	S075TPABSBKGP
S075TPSBSGP	S075TPSBSBKGP
S100TPABSGP	S100TPABSBKGP
S100TPSBSGP	S100TPSBSBKGP
S125TPABSGP	S125TPABSBKGP
S125TPSBSGP	S125TPSBSBKGP
S150TPABSGP	S150TPABSBKGP
S150TPSBSGP	S150TPSBSBKGP

code

≡ Plain bearing
□◻ Single precision bearing



support
type **M-S**

WHEEL
SERIES
TP

TPA-EQ TPA-ER TP-E TP-E

Support: Steel

Wheel: Grey rubber non marking, 82shA polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Single precision bearing

Type of fitting: Expander square for tubes 21/24mm, 24/27mm, 27/31mm, 31/35mm, 35/40mm
Expander round for tubes 19/23mm, 23/26mm, 26/30mm

Threadguards: Plastic threadguards

ERSBKGP

EXPANDER ROUND
SWIVEL WITH BREAK

EQSBKGP


EXPANDER SQUARE
SWIVEL WITH BREAK

EQSGP

EXPANDER SQUARE SWIVEL

ERSGP

EXPANDER ROUND SWIVEL



50	24	73.5	25	77	50	==
50	24	73.5	25	77	50	□□
75	24	101	30.5	86	60	==
75	24	101	30.5	86	60	□□
100	24	123.5	40	101	70	==
100	24	123.5	40	101	70	□□
125	24	148.5	43	104	80	==
125	24	148.5	43	104	80	□□

75	32	109	28	95	70	==
75	32	109	28	95	70	□□
100	32	131.5	40	107	90	==
100	32	131.5	40	107	90	□□
125	32	156.5	40	107	100	==
125	32	156.5	40	107	100	□□
150	32	181.5	45	112	100	==
150	32	181.5	45	112	100	□□

mm

kg



M050TPAEQS()GP	M050TPAEQS()BKGP	M050TPAERS()G	M050TPAERS()BKGP
M050TPSEQS()GP	M050TPSEQS()BKGP	M050TPSERS()G	M050TPSERS()BKGP
M075TPAEQS()GP	M075TPAEQS()BKGP	M075TPAERS()G	M075TPAERS()BKGP
M075TPSEQS()GP	M075TPSEQS()BKGP	M075TPSERS()G	M075TPSERS()BKGP
M100TPAEQS()GP	M100TPAEQS()BKGP	M100TPAERS()G	M100TPAERS()BKGP
M100TPSEQS()GP	M100TPSEQS()BKGP	M100TPSERS()G	M100TPSERS()BKGP
M125TPAEQS()GP	M125TPAEQS()BKGP	M125TPAERS()G	M125TPAERS()BKGP
M125TPSEQS()GP	M125TPSEQS()BKGP	M125TPSERS()G	M125TPSERS()BKGP
S075TPAEQS()GP	S075TPAEQS()BKGP	S075TPAERS()GP	S075TPAERS()BKGP
S075TPSEQS()GP	S075TPSEQS()BKGP	S075TPSERS()GP	S075TPSERS()BKGP
S100TPAEQS()GP	S100TPAEQS()BKGP	S100TPAERS()GP	S100TPAERS()BKGP
S100TPSEQS()GP	S100TPSEQS()BKGP	S100TPSERS()GP	S100TPSERS()BKGP
S125TPAEQS()GP	S125TPAEQS()BKGP	S125TPAERS()GP	S125TPAERS()BKGP
S125TPSEQS()GP	S125TPSEQS()BKGP	S125TPSERS()GP	S125TPSERS()BKGP
S150TPAEQS()GP	S150TPAEQS()BKGP	S150TPAERS()GP	S150TPAERS()BKGP
S150TPSEQS()GP	S150TPSEQS()BKGP	S150TPSERS()GP	S150TPSERS()BKGP

code

== Plain bearing

□□ Single precision bearing

Notice:

To get the complete article Nr, just fill in the bracket the requested dimension e.g for Square expander for tube 21/24mm, the article Nr is **M050TPAEQS(21/24)GP** while for round expander for tube 23/26mm, the article Nr is **M050TPAERS(23/26)GP**



TPA
PLAIN BEARING

TPC/TPX
BALL BEARINGS



50	24	8	28	50	≡
50	24	8	28	50	◻◻
75	24	8	28	60	≡
75	24	8	28	60	◻◻
100	24	8	28	70	≡
100	24	8	28	70	◻◻
125	24	8	28	80	≡
125	24	8	28	80	◻◻
75	32	10	36	70	≡
75	32	10	36	70	◻◻
100	32	10	36	90	≡
100	32	10	36	90	◻◻
125	32	10	36	100	≡
125	32	10	36	100	◻◻
150	32	10	36	100	≡
150	32	10	36	100	◻◻

mm

kg

Properties

Resistance to chemicals

Resistance in wet conditions

Long service life

Notes

For stainless steel bearings you have to switch the TPC part of the code to TPX

≡ Plain bearing
◻◻ Double ball bearing

M series
Medium range

S series
Heavier range

STAINLESS STEEL

TPA-T TPC-T

Support: Stainless Steel (AISI 304)

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Top plate for M series 60x60mm (43x49 / 43x49mm)
for S series 90x70mm (65x45 / 75x55mm)



TPSBK

TOP PLATE SWIVEL WITH BREAK




TF

TOP PLATE FIXED



TS

TOP PLATE SWIVEL



M series
Medium range

50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	—
50	24	60X60	43X49/43X49	6,4	73,5	25	77	50	□□
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	—
75	24	60X60	43X49/43X49	6,4	101	30,5	86	60	□□
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	—
100	24	60X60	43X49/43X49	6,4	123,5	40	101	70	□□
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	—
125	24	60X60	43X49/43X49	6,4	148,5	43	104	80	□□

S series
Heavier range

75	32	90X70	65X45/75X55	9	109	28	95	70	—
75	32	90X70	65X45/75X55	9	109	28	95	70	□□
100	32	90X70	65X45/75X55	9	131,5	40	107	90	—
100	32	90X70	65X45/75X55	9	131,5	40	107	90	□□
125	32	90X70	65X45/75X55	9	156,5	40	107	100	—
125	32	90X70	65X45/75X55	9	156,5	40	107	100	□□
150	32	90X70	65X45/75X55	9	181,5	45	112	100	—
150	32	90X70	65X45/75X55	9	181,5	45	112	100	□□

MX050TPATS	MX050TPATSBK	MX050TPATF
MX050TPCTS	MX050TPCTSBK	MX050TPCTF
MX075TPATS	MX075TPATSBK	MX075TPATF
MX075TPCTS	MX075TPCTSBK	MX075TPCTF
MX100TPATS	MX100TPATSBK	MX100TPATF
MX100TPCTS	MX100TPCTSBK	MX100TPCTF
MX125TPATS	MX125TPATSBK	MX125TPATF
MX125TPCTS	MX125TPCTSBK	MX125TPCTF

SX075TPATS	SX075TPATSBK	SX075TPATF
SX075TPCTS	SX075TPCTSBK	SX075TPCTF
SX100TPATS	SX100TPATSBK	SX100TPATF
SX100TPCTS	SX100TPCTSBK	SX100TPCTF
SX125TPATS	SX125TPATSBK	SX125TPATF
SX125TPCTS	SX125TPCTSBK	SX125TPCTF
SX150TPATS	SX150TPATSBK	SX150TPATF
SX150TPCTS	SX150TPCTSBK	SX150TPCTF

mm

kg


code

— Plain bearing

□□ Double ball bearing

Notice:

For stainless steel bearings you have to switch the TPC part of the code to TPX



support
type

M-S

WHEEL
SERIES
TP

STAINLESS STEEL

TPA-H TPC-H

Support: Stainless Steel (AISI 304)

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: Hole fitting For M series, bolt hole fitting 10,2mm
For S series, bolt hole fitting 12,2mm

Plastic threadguards



HSBK

HOLE FITTING SWIVEL WITH BREAK



HF

HOLE FITTING FIXED



HS

HOLE FITTING SWIVEL



50	24	10,2	73,5	25	77	50	—
50	24	10,2	73,5	25	77	50	●●
75	24	10,2	101	30,5	86	60	—
75	24	10,2	101	30,5	86	60	●●
100	24	10,2	123,5	40	101	70	—
100	24	10,2	123,5	40	101	70	●●
125	24	10,2	148,5	43	104	80	—
125	24	10,2	148,5	43	104	80	●●
75	32	12,2	109	28	95	70	—
75	32	12,2	109	28	95	70	●●
100	32	12,2	131,5	40	107	90	—
100	32	12,2	131,5	40	107	90	●●
125	32	12,2	156,5	40	107	100	—
125	32	12,2	156,5	40	107	100	●●
150	32	12,2	181,5	45	112	100	—
150	32	12,2	181,5	45	112	100	●●

mm

kg

MX050TPAHS	MX050TPAHSBK	MX050TPAHF
MX050TPCHS	MX050TPCHSBK	MX050TPCHF
MX075TPAHS	MX075TPAHSBK	MX075TPAHF
MX075TPCHS	MX075TPCHSBK	MX075TPCHF
MX100TPAHS	MX100TPAHSBK	MX100TPAHF
MX100TPCHS	MX100TPCHSBK	MX100TPCHF
MX125TPAHS	MX125TPAHSBK	MX125TPAHF
MX125TPCHS	MX125TPCHSBK	MX125TPCHF
SX075TPAHS	SX075TPAHSBK	SX075TPAHF
SX075TPCHS	SX075TPCHSBK	SX075TPCHF
SX100TPAHS	SX100TPAHSBK	SX100TPAHF
SX100TPCHS	SX100TPCHSBK	SX100TPCHF
SX125TPAHS	SX125TPAHSBK	SX125TPAHF
SX125TPCHS	SX125TPCHSBK	SX125TPCHF
SX150TPAHS	SX150TPAHSBK	SX150TPAHF
SX150TPCHS	SX150TPCHSBK	SX150TPCHF

code

— Plain bearing

●● Double ball bearing



Stainless Steel

Notice:

For stainless steel bearings you have to switch the TPC part of the code to TPX

STAINLESS STEEL

TPA-B TPC-B

Support: Stainless Steel (AISI 304)

Wheel: Grey rubber non marking 82shA, polypropylene rim
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing

Type of fitting: for the M series, Bolt stem M10X20 | Different bolt stems available
for the S series, Bolt stem M12X25 | (M08X25, M10X30 etc)



BSBK

BOLT STEM SWIVEL WITH BREAK



BS

BOLT STEM SWIVEL



M series
Medium range

S series
Heavier range

50	24	M10X20	73,5	25	77	50	■
50	24	M10X20	73,5	25	77	50	■
75	24	M10X20	101	30,5	86	60	■
75	24	M10X20	101	30,5	86	60	■
100	24	M10X20	123,5	40	101	70	■
100	24	M10X20	123,5	40	101	70	■
125	24	M10X20	148,5	43	104	80	■
125	24	M10X20	148,5	43	104	80	■
75	32	M12X25	109	28	95	70	■
75	32	M12X25	109	28	95	70	■
100	32	M12X25	131,5	40	107	90	■
100	32	M12X25	131,5	40	107	90	■
125	32	M12X25	156,5	40	107	100	■
125	32	M12X25	156,5	40	107	100	■
150	32	M12X25	181,5	45	112	100	■
150	32	M12X25	181,5	45	112	100	■

mm

kg

MX050TPABS	MX050TPABSBK
MX050TPCBS	MX050TPCBSBK
MX075TPABS	MX075TPABSBK
MX075TPCBS	MX075TPCBSBK
MX100TPABS	MX100TPABSBK
MX100TPCBS	MX100TPCBSBK
MX125TPABS	MX125TPABSBK
MX125TPCBS	MX125TPCBSBK

SX075TPABS	SX075TPABSBK
SX075TPCBS	SX075TPCBSBK
SX100TPABS	SX100TPABSBK
SX100TPCBS	SX100TPCBSBK
SX125TPABS	SX125TPABSBK
SX125TPCBS	SX125TPCBSBK
SX150TPABS	SX150TPABSBK
SX150TPCBS	SX150TPCBSBK


code

■ Plain bearing

■ Double ball bearing

Notice:

For stainless steel bearings you have to switch the TPC part of the code to TPX



support
type

M-S

WHEEL SERIES TP



Stainless Steel

TPA-EQ TPA-ER TPC-EQ TPC-ER

STAINLESS STEEL

Support: Stainless Steel (AISI 304)

Wheel: Grey rubber non marking, 82shA
(available also in different hardness 55shA, 72shA, etc)

Axle material: Plain bearing
Ball bearing


Type of fitting: Expander square for tubes 21/24mm, 24/27mm, 27/31mm, 31/35mm, 35/40mm
Expander round for tubes 19/23mm, 23/26mm, 26/30mm

ERSBK
EXPANDER ROUND WITH BREAK

EQSBK
EXPANDER SQUARE WITH BREAK

EQS
EXPANDER SQUARE

ERS
EXPANDER ROUND



50	24	73.5	25	77	50	==
50	24	73.5	25	77	50	□□
75	24	101	30.5	86	60	==
75	24	101	30.5	86	60	□□
100	24	123.5	40	101	70	==
100	24	123.5	40	101	70	□□
125	24	148.5	43	104	80	==
125	24	148.5	43	104	80	□□

75	32	109	28	95	70	==
75	32	109	28	95	70	□□
100	32	131.5	40	107	90	==
100	32	131.5	40	107	90	□□
125	32	156.5	40	107	100	==
125	32	156.5	40	107	100	□□
150	32	181.5	45	112	100	==
150	32	181.5	45	112	100	□□

mm

kg



M050TPAEQS()GX	M050TPAEQS()BKGX	M050TPAERS()GX	M050TPAERS()BKGX
M050TPCEQS()GX	M050TPCEQS()BKGX	M050TPCERS()GX	M050TPCERS()BKGX
M075TPAEQS()GX	M075TPAEQS()BKGX	M075TPAERS()GX	M075TPAERS()BKGX
M075TPCEQS()GX	M075TPCEQS()BKGX	M075TPCERS()GX	M075TPCERS()BKGX
M100TPAEQS()GX	M100TPAEQS()BKGX	M100TPAERS()GX	M100TPAERS()BKGX
M100TPCEQS()GX	M100TPCEQS()BKGX	M100TPCERS()GX	M100TPCERS()BKGX
M125TPAEQS()GX	M125TPAEQS()BKGX	M125TPAERS()GX	M125TPAERS()BKGX
M125TPCEQS()GX	M125TPCEQS()BKGX	M125TPCERS()GX	M125TPCERS()BKGX
SX075TPAEQS()GX	SX075TPAEQS()BKGX	SX075TPAERS()GX	SX075TPAERS()BKGX
SX075TPCEQS()GX	SX075TPCEQS()BKGX	SX075TPCERS()GX	SX075TPCERS()BKGX
SX100TPAEQS()GX	SX100TPAEQS()BKGX	SX100TPAERS()GX	SX100TPAERS()BKGX
SX100TPCEQS()GX	SX100TPCEQS()BKGX	SX100TPCERS()GX	SX100TPCERS()BKGX
SX125TPAEQS()GX	SX125TPAEQS()BKGX	SX125TPAERS()GX	SX125TPAERS()BKGX
SX125TPCEQS()GX	SX125TPCEQS()BKGX	SX125TPCERS()GX	SX125TPCERS()BKGX
SX150TPAEQS()GX	SX150TPAEQS()BKGX	SX150TPAERS()GX	SX150TPAERS()BKGX
SX150TPCEQS()GX	SX150TPCEQS()BKGX	SX150TPCERS()GX	SX150TPCERS()BKGX

code

== Plain bearing

□□ Double ball bearing

Notice:

To get the complete article Nr, just fill in the bracket the requested dimension e.g for Square expander for tube 21/24mm, the article Nr is **M050TPAEQS(21/24)** while for round expander for tube 23/26mm, the article Nr is **M050TPAERS(23/26)**

For stainless steel bearings you have to switch the TPC part of the code to TPX



Stainless Steel


WITH STAINLESS
THREAD GUARDS



TPA-GX & TPC/TPX-GX

PLAIN BEARING

BALL BEARINGS



Properties

Resistance to chemicals

Resistance in wet conditions

Long service life

Notes

For stainless steel bearings you have to switch the TPC part of the code to TPX

 Plain bearing
 Double ball bearing

M series
Medium range

50	24	8	28	50	
50	24	8	28	50	
75	24	8	28	60	
75	24	8	28	60	
100	24	8	28	70	
100	24	8	28	70	
125	24	8	28	80	
125	24	8	28	80	

WLTPA050M
 WLTPC050M
 WLTPA075M
 WLTPC075M
 WLTPA100M
 WLTPC100M
 WLTPA125M
 WLTPC125M

S series
Heavier range

75	32	10	36	70	
75	32	10	36	70	
100	32	10	36	90	
100	32	10	36	90	
125	32	10	36	100	
125	32	10	36	100	
150	32	10	36	100	
150	32	10	36	100	

WLTPA075S
 WLTPC075S
 WLTPA100S
 WLTPC100S
 WLTPA125S
 WLTPC125S
 WLTPA150S
 WLTPC150S

mm

kg