


100W / 200W LASER CLEANING MACHINE

SMALL / LIGHT AND COMPACT / FLEXIBLE USE



OUR ADVANTAGE



27-inch trolley case control system:
Built-in laser, laser head and accessories




USE Directly on Power
Universal 220V power supply, plug and play



One-Touch operation
Easy operation
Advanced user & normal user dual operation interface



Environmental Friendly
The most environmentally friendly industrial cleaning method



International famous brand Components



First-rate service
24-hour service



Dual use laser head
handheld & robotic hold
switching time < 5 seconds




Global Top Technology Support
Comprehensive process technical support from Doctor and Master team

TECHNOLOGY UPGRADED

The fourth generation dual purpose laser head Handheld and automatic 2D laser head

Easy to hold and integrate with automation;
Easy to operate and has various functions



Indicator light, safety lock
Laser emission indicator, safety lock to ensure process safety

Automatic mode adapter plate
Manual / automatic switching time less than 5s

Positioning hole
Manual mode auxiliary processing device positioning hole

Manual mode auxiliary processing device
Easy to handheld and control the cleaning focus point

Heat sink
With cooling fan, to ensure stable operation of the laser head

Cooling hole
With cooling hole, to ensure stable operation of the laser head

Auto mode snap ring
Easy installation easy operation

Lighting device
With lighting device, it can be applied in poor light environment

Focus Lens
160/254/330/420 for optional, suitable for various situations. Can scan straight line, circle, spiral, rectangle, square, round fill, rectangular fill etc. It can deal the appropriate scanning pattern according to customer demand

laser source connection
Suitable for isolator, QCS, QBH commonly used laser connectors in the market


Lightweight and convenient
The laser head weighs only 823g

PK OTHER LASER HEADS




First

1. The volume is too large
2. Bulky
3. Difficult to handle



Second

1. The image has only straight line and spiral
2. Single fixed focal length
3. The knob is easy to be damaged and difficult to adjust the parameters
4. Bulky
5. Difficult to integrate automation



Third


1. Poor heat dissipation, long-term use will damage the galvanometer and lens
2. Without protection, it is easy to touch the launch button by mistake, causing harm
3. Not easy to integrate automation
4. The focus is difficult to control

AMPLE SOFTWARE PRESTORE OF VARIOUS PARAMETER GRAPHICS

1. Simple software, select prestored parameters directly
2. Prestore all kinds of parameter graphics, six kinds of graphics can be selected: straight line/spiral/circle/rectangle/rectangle filling/Circle filling
3. Easy to use and operate
4. Simple interface
5. 12 different modes can be switched and selected quickly to facilitate production and debugging
6. The language can be English/Chinese or other languages (if required)




SCANNABLE GRAPHICS



HIGH QUALITY PARTS

Stable and efficient imported / domestic famous brands (RAYCUS or IPG / Siemens / Weichuang, etc.) accessories and components are adopted to ensure the stable and reliable operation of the equipment. Easy to operate, complete and diverse functions.





USE Directly on Power

Universal 220V power supply, plug and play

Environmental Friendly

The most environmentally friendly industrial cleaning method,
Portable dust auxiliary treatment system (optional).



TECHNICAL PARAMETERS

Max average power(W)	100	200
Output central wavelength(nm)	1064±5	1064±5
Beam quality(M ²)	≤1.6	≤1.8
Power adjustment range(%)	10-100	10-100
Output power instability(%)	≤5	≤5
Pulse repetition rate(KHz)	20-400	20-2000
Pulse length(ns)	10/20/30/60/100/200/250/350 Optional	10/30/60/240 Optional
Max pulse energy(mJ)	1	1
Fibre length(m)	3	3/5
Laser safety classification	4	4
cooling method	Air-cooled	Air-cooled

TROLLEY CASE FUNCTION INTRODUCTION



Trolley
Hand-drawn box design, more convenient to carry and move

Key switch
Prevent unrelated personnel from accidentally opening

Siemens safety emergency stop switch

Display screen
More compact, double-layer screen protection film, removable surface protection film, more dustproof, cleaner, and scratch-resistant

EVA material environmental protection
Environmental protection soft, beautiful, stable, fireproof, durable

Power cable

Glasses cleaning towel
Convenient and fast to remove dust and dirt

Laser head
Four generations of unique upgrades

Portable handle
Two handle sides, with the bottom of the metal handle to facilitate its side, a double lifting and easy one-handed double or single lifting and pulling

Display lamp
Three-color light, red is working state, yellow is ready working state, green is normal state, which is more striking

Winding protection cable
Unique design, more beautiful, more tensile, more resistant to fall, more resistant to dirt, easier to clean

Optional Lens
F160/F254/F330 for optional

Special laser protective glasses
Professional laser protective glasses, clearer, safer and more reliable

Air inlet filter
Unique design portable removable air filter, better air intake, anti-dust, better air intake, dustproof and anti dirty, easy to disassemble and maintain

Shockproof foot pad
Unique European standard design, anti dumping, more stable and stand reliable

Double layer screen protector
Easy to remove protective film on the surface, better dustproof, cleaner, more scratch resistant

Fuse
Unique safety design and external fuse make it safer, more reliable and more convenient to replace

12-Pin Waterproof Plug
Waterproof, safe, reliable, easy to program upgrade

Main power connector
Easy to carry, easy to disassemble

4-Pin Waterproof Plug
Waterproof, safe, reliable, convenient for external series connection, convenient for automatic docking

The box door can rotate freely with 270° opening, which is more convenient to use



Bottom metal handle with side double handle, easy to side down, double lift/easy to double single hand lift or single lift

MODEL LIVE SHOW



Small


Light and compac

Flexible use

length: 538mm width: 411mm height: 685mm

SAFETY SIGNS

Comply with GB 7247-2012/ IEC 60825-1:2007 safety standard
It conforms to per IEC 60825-1:2014 international laser safety level appraisal standard



Rust removal

scale cinder removal

Stainless steel polishing

layered paint removal

Laser texturing

Weld laser cleaning

Coating removal

Auto parts cleaning

oil removal

Use protective film, sponge, high shockproof foam board, etc.

Sealed in wooden case, moistureproof and shockproof

Export packing, easy to transport

APPLICATION CASES